



MOTOTRBO™

XPR™ 4500/4550/4300/4350 Mobile Radios



Mobile radios available in Display and Numeric Display, **GPS and Non-GPS models**

Uses Time-Division Multiple-Access (TDMA) digital technology which **doubles the number of users** you can have on a single licensed 12.5 kHz channel

Integrates voice and data to increase operational efficiency

Supports **integrated applications** including MOTOTRBO Text Messaging Services and MOTOTRBO Location Services

Provides **clearer voice communications** throughout the coverage area as compared to analog radios

Enables additional functionality including dispatch data, and enhanced call signaling

Enhanced call management features include call alert, emergency, remote monitor, push-to-talk ID, radio check, private call, all call and radio disable

Four programmable buttons (two buttons for XPR 4300/4350) for **easy access to favorite features**; Replacement Button Kit offers customized feature-specific buttons

Emergency button (or footswitch) **alerts supervisor** or dispatcher in emergency situations

Multi-colored LED indicators for **clear, visible feedback** of calling, scanning and monitoring features

XPR 4550/4350 **location coordinates** can be sent to dispatcher when emergency button is pressed

Allows **easy migration** from analog to digital as all units operate in analog and digital modes

Meets U.S. Military Standards 810 C, D, E, and F, and **Motorola standards** for durability and reliability

Newly designed and durable IMPRES™ keypad microphone supports unit to unit **short free form and quick text messaging**

Utilizes the IMPRES Audio System for **enhanced audio functionality**

Backed by a two-year Standard Warranty plus one-year **Repair Service Advantage** (US) / Extended Warranty (Canada) and at least a one-year warranty for accessories

Send short free-form (requires keypad microphone) and quick **text messaging** via programmable buttons

XPR 4500/4550 contacts list accommodates up to **256 contacts**

Accelerate performance.

The next-generation professional two-way radio communications solution is here, with more performance, productivity and value—thanks to digital technology that delivers increased capacity and spectrum efficiency, integrated data communications and enhanced voice communications.

MOTOTRBO offers you a private, standards-based, cost-effective solution that can be tailored to meet your unique coverage and feature needs. This versatile portfolio provides a complete system of portable radios, mobile radios, repeaters, accessories and data applications.

General Specifications

	Display XPR 4500 / XPR 4550		Numeric Display XPR 4300 / XPR 4350	
	136-174 MHz	403-470 MHz	136-174 MHz	403-470 MHz
Channel Capacity	160		32	
Typical RF Output				
Low Power	1-25 W*	1-25 W	1-25 W*	1-25 W
High Power	25-45 W	25-40 W	25-45 W*	25-40 W
Frequency	136-174 MHz	403-470 MHz	136-174 MHz	403-470 MHz
Dimensions (HxWxL)	2.01 x 6.89 x 8.11 in (51 x 175 x 206 mm)		2.01 x 6.89 x 8.11 in (51 x 175 x 206 mm)	
Weight	4.0 lbs. (1.8 kg)		4.0 lbs. (1.8 kg)	
Current Drain:				
Standby	0.81 A max	0.81 A max	0.81 A max	0.81 A max
Rx @ Rated Audio	2 A max	2 A max	2 A max	2 A max
Transmit	1-25 W - 11.0 A max 25-45 W - 14.5 A max	1-25 W - 11.0 A max 25-40 W - 14.5 A max	1-25 W - 11.0 A max 25-45 W - 14.5 A max	1-25 W - 11.0 A max 25-40 W - 14.5 A max
FCC Description	1-25 W - ABZ99FT3083 25-45 W - ABZ99FT3082	1-25 W - ABZ99FT4081 25-40 W - ABZ99FT4080	1-25 W - ABZ99FT3083 25-45 W - ABZ99FT3082	1-25 W - ABZ99FT4081 25-40 W - ABZ99FT4080
IC Description	1-25 W - 109AB-99FT3083 25-45 W - 109AB-99FT3082	1-25 W - 109AB-99FT4081 25-40 W - 109AB-99FT4080	1-25 W - 109AB-99FT3083 25-45 W - 109AB-99FT3082	1-25 W - 109AB-99FT4081 25-40 W - 109AB-99FT4080

Receiver

	136-174 MHz		403-470 MHz	
	136-174 MHz	403-470 MHz	136-174 MHz	403-470 MHz
Frequencies	136-174 MHz		403-470 MHz	
Channel Spacing	12.5 kHz / 25 kHz		12.5 kHz / 25 kHz	
Frequency Stability	+/- 1.5 ppm (XPR 4500) +/- 0.5 ppm (XPR 4550)		+/- 1.5 ppm (XPR 4300) +/- 0.5 ppm (XPR 4350)	
Analog Sensitivity (12dB SINAD)	0.3 uV 0.22 uV (typical)		0.3 uV 0.22 uV (typical)	
Digital Sensitivity	5% BER: 0.3 uV		5% BER: 0.3 uV	
Intermodulation (TIA603C)	78 dB	75 dB	78 dB	75 dB
Adjacent Channel Selectivity				
TIA603	65 dB @ 12.5 kHz, 80 dB @ 25 kHz	65 dB @ 12.5 kHz, 75 dB @ 25 kHz	65 dB @ 12.5 kHz, 80 dB @ 25 kHz	65 dB @ 12.5 kHz, 75 dB @ 25 kHz
TIA603C	50 dB @ 12.5 kHz, 80 dB @ 25 kHz	50 dB @ 12.5 kHz, 75 dB @ 25 kHz	50 dB @ 12.5 kHz, 80 dB @ 25 kHz	50 dB @ 12.5 kHz, 75 dB @ 25 kHz
Spurious Rejection (TIA603C)	80 dB	75 dB	80 dB	75 dB
Rated Audio	3 W (Internal) 7.5 W (External - 8 ohms) 13 W (External - 4 ohms)		3 W (Internal) 7.5 W (External - 8 ohms) 13 W (External - 4 ohms)	
Audio Distortion @ Rated Audio	3% (typical)		3% (typical)	
Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz		-40 dB @ 12.5 kHz -45 dB @ 25 kHz	
Audio Response	TIA603C		TIA603C	

Transmitter

	136-174 MHz		403-470 MHz	
	136-174 MHz	403-470 MHz	136-174 MHz	403-470 MHz
Frequencies	136-174 MHz		403-470 MHz	
Channel Spacing	12.5 kHz / 25 kHz		12.5 kHz / 25 kHz	
Frequency Stability	+/- 1.5 ppm (XPR 4500) +/- 0.5 ppm (XPR 4550)		+/- 1.5 ppm (XPR 4300) +/- 0.5 ppm (XPR 4350)	
Power Output				
Low Power	1-25 W*	1-25 W	1-25 W*	1-25 W
High Power	25-45 W	25-40 W	25-45 W*	25-40 W
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz +/- 5.0 kHz @ 25 kHz		+/- 2.5 kHz @ 12.5 kHz +/- 5.0 kHz @ 25 kHz	
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz		-40 dB @ 12.5 kHz -45 dB @ 25 kHz	
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz		-36 dBm < 1 GHz -30 dBm > 1 GHz	
Adjacent Channel Power (TIA603C)	80 dB @ 12.5 kHz 70 dB @ 25 kHz		80 dB @ 12.5 kHz 70 dB @ 25 kHz	
Audio Response	TIA603C		TIA603C	
Audio Distortion	3%		3%	
FM Modulation	12.5 kHz: 11K0F3E 25 kHz: 16K0F3E		12.5 kHz: 11K0F3E 25 kHz: 16K0F3E	
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE		12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE	
Digital Vocoder Type	AMBE++		AMBE++	
Digital Protocol	ETSI-TS102 361-1		ETSI-TS102 361-1	

GPS

Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength).

TTFF (Time to First Fix) Cold Start	< 1 minute
TTFF (Time to First Fix) Hot Start	< 10 seconds
Horizontal Accuracy	< 10 meters

*Coming Soon.

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.
Version 4 07/07

Environmental Specifications

Operating Temperature	-30° C / +60° C
Storage Temperature	-40° C / +85° C
Thermal Shock	Per MIL-STD
Humidity	Per MIL-STD
ESD	IEC-801-2KV
Water Intrusion	IEC 60529 - IP57
Packaging Test	MIL-STD 810D and E



MOTOROLA
Authorized Dealer & Service Center



ANCOM Communications & Technical Center

1800 E Cliff Road, Suite 17
Burnsville, MN 55337
952-808-0033 main
952-808-0034 fax
sales@ancom.org

ancom.radio-dealers.com

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their registered owners. © Motorola, Inc. 2007
MD-EU/SP/MOBILE