



# MOTOTRBO™

## XPR™ 8300 Repeater



Supports **two simultaneous voice or data paths** in digital Time-Division Multiple-Access (TDMA) mode

**100% continuous full duty cycle** at 40W/UHF and 45W/VHF

**Integrated** power supply

Operates in **analog or digital** mode—bright, clear, colored LEDs

indicate mode LEDs clearly indicate **transmit and receive modes** in both channel slots

**Rack or wall-mountable**; desktop housing also available

**Sturdy handles** make installation and handling easier

**Automated** battery back-up (battery sold separately)

The MOTOTRBO system is backed by a **two-year** Standard Warranty

**Doubles the number of users** you can have on a single licensed 12.5 kHz channel

**Integrates voice and data** to increase operational efficiency

**Supports integrated applications** including MOTOTRBO Text Messaging Services and MOTOTRBO Location Services (GPS location tracking)

MOTOTRBO is a **complete two-way radio system** that includes portable and mobile radios, repeaters, accessories and applications

### Accelerate performance.

The next-generation professional two-way radio communications solution is here, with more performance, productivity and value—thanks to digital technology that delivers increased capacity and spectrum efficiency, integrated data communications and enhanced voice communications.

MOTOTRBO offers you a private, standards-based, cost-effective solution that can be tailored to meet your unique coverage and feature needs. This versatile portfolio provides a complete system of portable radios, mobile radios, repeaters, accessories and data applications.

## General Specifications

Technical RF Output	1-25 W*	1-25 W*
Current Drain During Standby: Low Power	1 A (1 A DC typical)*	
Current Drain During Transmit: Low Power	3 A (10 A DC typical)*	
FCC Description	ABZ99FT3025	ABZ99FT4025
IC Description	109AB-99FT3025	109AB-99FT4025

## Receiver

	136-174 MHz	403-470 MHz
Frequencies	136-174 MHz	403-470 MHz
Channel Spacing	12.5 kHz / 25 kHz	
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm	
Analog Sensitivity (12 dB SINAD)	0.30 uV 0.22 uV (typical)	
Digital Sensitivity	5% BER: 0.3 uV	
Intermodulation (TIA603C)	78 dB	75 dB
Adjacent Channel Selectivity: TIA603 TIA603C	65 dB @ 12.5 kHz, 80 dB @ 25 kHz 50 dB @ 12.5 kHz, 80 dB @ 25 kHz	65 dB @ 12.5 kHz, 75 dB @ 25 kHz 50 dB @ 12.5 kHz, 75 dB @ 25 kHz
Spurious Rejection	75 dB	
Audio Distortion @ Rated Audio	3% (typical)	
Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz	
Audio Response	TIA603C	
Conducted Spurious Emission	-57 dBm	

## Transmitter

	136-174 MHz	403-470 MHz
Frequencies	136-174 MHz	403-470 MHz
Channel Spacing	12.5 kHz / 25 kHz	
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm	
Power Output: Low Power High Power	1-25 W* 25-45 W	1-25 W* 25-40 W
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz +/- 5.0 kHz @ 25 kHz	
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz	
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz	
Adjacent Channel Power (TIA603C)	60 dB @ 12.5 kHz 70 dB @ 25 kHz	
Audio Response	TIA603C	
Audio Distortion	3%	
FM Modulation	12.5 kHz: 11K0F3E 25 kHz: 16K0F3E	
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE	
Digital Vocoder Type	AMBE++	
Digital Protocol *Coming soon.	ETSI-TS102 361-1	

Specifications subject to change without notice. All specifications shown are typical.

Radio meets applicable regulatory requirements.

Version 4 07/07



**MOTOROLA**  
Authorized Dealer & Service Center



### ANCOM Communications

1800 E Cliff Road, Suite 17  
Burnsville, MN 55337  
952-808-0033 main  
952-808-0034 fax  
sales@ancom.org  
ancom.radio-dealers.com

### ANCOM Technical Center

1800 E Cliff Road, Suite 17  
Burnsville MN 55337  
952-808-7699 main  
952-808-0034 fax  
service@ancom.org